











































Assembled 40mm, IP 65, UL Type 4

Plastic
Limit switches

30° Cam transl.		30° Cam translation movement			
					
Stainless steel roller lever	Ball-bearing roller lever	Ø 22 Polyamide roller lever	Ø 22 Stainless steel roller lever	Ø 22 Ball-bearing roller lever	Ø 45 Rubber roller lever
1 12 N 40 N	1 12 N 40 N	EN 50 041 1.5 0.15 N.m 0.44 N.m	EN 50 041 1.5 0.15 N.m 0.44 N.m	EN 50 041 1.5 0.15 N.m 0.44 N.m	1.5 0.15 N.m -

9

LS45P32B11 \$ 39	LS45P33B11 \$ 36	LS45P41B11 \$ 39	LS45P42B11 \$ 47	LS45P43B11 \$ 42	LS45P44B11 \$ 41
					
LS45P32D11 42	LS45P33D11 38	LS45P41D11 42	LS45P42D11 50	LS45P43D11 45	LS45P44D11 44
					
LS45P32C11 43	LS45P33C11 39	LS45P41C11 43	LS45P42C11 52	LS45P43C11 47	LS45P44C11 45
					
LS45P32L02 43	LS45P33L02 39	LS45P41L02 43	LS45P42L02 52	LS45P43L02 47	LS45P44L02 45
					
LS45P32L20 43	LS45P33L20 39	LS45P41L20 43	LS45P42L20 52	LS45P43L20 47	LS45P44L20 45
					
LS45P32B02 43	LS45P33B02 39	LS45P41B02 43	LS45P42B02 52	LS45P43B02 47	LS45P44B02 45
					
0.185	0.185	0.185	0.195	0.195	0.205

Dimensions (in mm)

