

Assembled IP66, UL Type 4X 40mm

Movement to be detected

Unidirectional

30° Cam translation movement



Operating head type

	ø 22 Ball-bearing roller lever	ø 22 Polyamide roller lever	ø 22 Stainless steel roller lever	ø 22 Ball-bearing roller lever
Conformity / \ominus (N.C. contact with positive opening operation)		EN 50 041	EN 50 041	EN 50 041
Maximum actuation speed m/s	1.5	1.5	1.5	1.5
Min. force/torque:				
- actuation	12 N	0.15 N.m	0.15 N.m	0.15 N.m
- positive opening operation	40 N	0.44 N.m	0.44 N.m	0.44 N.m

9

	LS45M33B11 \$ 45	LS45M41B11 \$ 50	LS45M42B11 \$ 57	LS45M43B11 \$ 53	
Snap action contacts 	Catalog number List price	LS45M33D11 49	LS45M41D11 53	LS45M42D11 61	LS45M43D11 57
Non-overlapping slow action contacts 	Catalog number List price	LS45M33C11 50	LS45M41C11 55	LS45M42C11 63	LS45M43C11 58
Overlapping slow action contacts 	Catalog number List price	LS45M33L02 50	LS45M41L02 55	LS45M42L02 63	LS45M43L02 58
Slow action contacts 	Catalog number List price	LS45M33L20 50	LS45M41L20 55	LS45M42L20 63	LS45M43L20 58
Slow action contacts 	Catalog number List price	LS45M33B02 50	LS45M41B02 55	LS45M42B02 63	LS45M43B02 58
Snap action contacts 	Catalog number List price	Weight (packing per unit) kg			
		0.280	0.280	0.280	0.280

Dimensions (mm)

