

Assembled IP66, UL Type 4X 40mm

Movement to be detected



Operating head type

	Adjustable \varnothing 45 rubber roller lever	Flexible lever with insulated end	Coil spring lever	Adjustable \varnothing 3 stainless steel rod lever
Conformity / (N.C. contact with positive opening operation)				EN 50 041
Maximum actuation speed	m/s 1.5	m/s 1.5	m/s 1.5	m/s 0.5
Min. torque: - actuation	N.m 0.15	N.m 0.15	N.m 0.15	N.m 0.15
- positive opening operation	N.m -	N.m -	N.m -	N.m -

9

Snap action contacts	Catalog number	LS45M54B11	LS45M61B11	LS45M62B11	LS45M71B11
	List price	\$ 53	\$ 50	\$ 50	\$ 47
	Operation diagram				
Non-overlapping Slow action contacts	Catalog number	LS45M54D11	LS45M61D11	LS45M62D11	LS45M71D11
	List price	57	53	53	51
	Operation diagram				
Overlapping Slow action contacts	Catalog number	LS45M54C11	LS45M61C11	LS45M62C11	LS45M71C11
	List price	58	55	55	53
	Operation diagram				
Slow action contacts	Catalog number	LS45M54L02	LS45M61L02	LS45M62L02	LS45M71L02
	List price	58	55	55	53
	Operation diagram				
Slow action contacts	Catalog number	LS45M54L20	LS45M61L20	LS45M62L20	LS45M71L20
	List price	58	55	55	53
	Operation diagram				
Snap action contacts	Catalog number	LS45M54B02	LS45M61B02	LS45M62B02	LS45M71B02
	List price	58	55	55	53
	Operation diagram				
Weight (packing per unit)	kg	0.315	0.290	0.295	0.285

Dimensions (mm)

