

Assembled IP66, UL Type 4X 40mm

Metal
Limit switches

Movement to be detected

Translation (cont.)



Multidirectional



Operating head type

	Adjustable Ø 6 polyamide rod lever	Spring rod	Flexible rod with insulated end	Coil spring rod
Conformity / (N.C. contact with positive opening operation)	EN 50 041			
Maximum actuation speed	m/s 1.5	1	1	1
Min. torque: - actuation	N.m 0.15	0.18	0.18	0.18
- positive opening operation	N.m -	-	-	-

		LS45M72B11 \$ 47	LS45M91B11 \$ 41	LS45M92B11 \$ 43	LS45M93B11 \$ 42
Snap action contacts	Catalog number	LS45M72B11	LS45M91B11	LS45M92B11	LS45M93B11
	List price	\$ 47	\$ 41	\$ 43	\$ 42
	Operation diagram				
Non-overlapping Slow action contacts	Catalog number	LS45M72D11	LS45M91D11	LS45M92D11	LS45M93D11
	List price	50	43	46	45
	Operation diagram				
Overlapping Slow action contacts	Catalog number	LS45M72C11	LS45M91C11	LS45M92C11	LS45M93C11
	List price	52	45	47	47
	Operation diagram				
Slow action contacts	Catalog number	LS45M72L02	LS45M91L02	LS45M92L02	LS45M93L02
	List price	52	45	47	47
	Operation diagram				
Slow action contacts	Catalog number	LS45M72L20	LS45M91L20	LS45M92L20	LS45M93L20
	List price	52	45	47	47
	Operation diagram				
Snap action contacts	Catalog number	LS45M72B02	LS45M91B02	LS45M92B02	LS45M93B02
	List price	52	45	47	47
	Operation diagram				
Weight (packing per unit)	kg	0.285	0.235	0.235	0.235

Dimensions (mm)

