

Components

IP66, UL Type 4X

40mm

⊕ "N.C." contact with positive opening operation or element (subassembly, head, lever) suitable for positive opening operation.

Warning! The positive opening operation of limit switch is only guaranteed if the elements noted with ⊕ are fitted.



LSTE41



LSTE52



LSTE72

LSTE91



LSTE40



LSA40X41

	Positive opening operation	Actuation speed max. m/s	Unit weight kg (1 pc)	Catalog number	List price
Angular motion heads with actuator					
To be actuated by 30° cam					
∅ 22mm polyamide roller lever ①	⊕	1.5	0.134	LSTE41	\$ 26
∅ 22mm stainless steel roller lever ①	⊕	1.5	0.142	LSTE42	34
∅ 22mm steel ball-bearing roller lever ①	⊕	1.5	0.145	LSTE43	29
∅ 45mm rubber roller lever ①	⊕	1.5	0.162	LSTE44	28
∅ 22mm adjustable polyamide roller lever ①	⊗	1.5	0.152	LSTE51	27
∅ 22mm adjustable stainless steel roller lever ①	⊗	1.5	0.161	LSTE52	35
∅ 22mm adjustable steel ball-bearing roller lever ①	⊗	1.5	0.163	LSTE53	31
∅ 45mm adjustable rubber roller lever ①	⊗	1.5	0.168	LSTE54	29
To be actuated by fully directional translation movement					
Stainless steel flexible lever with insulated end ①	⊗	1	0.145	LSTE61	29
Stainless steel coil spring lever ①	⊗	1	0.152	LSTE62	29
∅ 3mm stainless steel rod lever, 195mm ①	⊗	1	0.150	LSTE71	26
∅ 6mm polyamide rod lever, 195mm ①	⊗	1	0.145	LSTE72	26
∅ 6mm fiberglass rod lever, 195mm ①	⊗	1	0.149	LSTE73	27
Multidirectional angular motion heads (to be actuated by fully directional translation movement)					
Stainless steel spring rod	⊗	1	0.066	LSTE91	17
Stainless steel flexible rod with insulated end	⊗	1	0.068	LSTE92	19
Stainless steel coil spring rod	⊗	1	0.075	LSTE93	18
Angular motion head without actuator, for non-adjustable roller levers (delivered with M5 nylon stop nut)					
	⊕	1.5	0.102	LSTE40	20
Actuators for angular motion head LSTE40					
∅ 22mm polyamide roller lever ①	⊕	—	0.032	LSA40X41	6
∅ 22mm stainless steel roller lever ①	⊕	—	0.042	LSA40X42	14
∅ 22mm steel ball-bearing roller lever ①	⊕	—	0.044	LSA40X43	9
∅ 45mm rubber roller lever ①	⊗	—	0.050	LSA40X44	8

① Free position adjustment of lever 9° by 9° over 360°