

Assembled IP66, UL Type 4X 60mm

Movement to be detected



Operating head type

	Stainless steel plain plunger	Stainless steel ball plunger	Stainless steel lateral plain plunger
Conformity / \ominus (N.C. contact with positive opening operation)	\ominus	\ominus	\ominus
Maximum actuation speed	0.5	0.5	0.5
Min. force: - actuation	22	22	30
- positive opening operation	66	66	70

9

Operating head type	Catalog number List price	Stainless steel plain plunger	Stainless steel ball plunger	Stainless steel lateral plain plunger
Snap action contacts 	LS65M11B11 \$ 40	LS65M12B11 \$ 42	LS65M21B11 \$ 42	
Non-overlapping Slow action contacts 	LS65M11D11 43	LS65M12D11 45	LS65M21D11 45	
Overlapping Slow action contacts 	LS65M11C11 44	LS65M12C11 47	LS65M21C11 47	
Slow action contacts 	LS65M11L02 44	LS65M12L02 47	LS65M21L02 47	
Slow action contacts 	LS65M11L20 44	LS65M12L20 47	LS65M21L20 47	
Snap action contacts 	LS65M11B02 44	LS65M12B02 47	LS65M21B02 47	
Weight (packing per unit)	kg	0.265	0.265	0.280

Dimensions (mm)

