

**Assembled  
IP66, UL Type 4X  
60mm**

**Movement to be detected**



**Operating head type**

|   | Adjustable $\varnothing$ 45 rubber roller lever | Flexible lever with insulated end | Coil spring lever |
|---|---|-----------------------------------|-------------------|
| Conformity / $\ominus$ (N.C. contact with positive opening operation) | ■   | ■                                 | ■                 |
| Maximum actuation speed   | 1.5 m/s   | 1.5 m/s                           | 1.5 m/s           |
| Min. torque: - actuation  | 0.15 N.m  | 0.15 N.m                          | 0.15 N.m          |
| - positive opening operation  | - N.m   | - N.m                             | - N.m             |

9

|                                      | Catalog number    | LS65M54B11 | LS65M61B11 | LS65M62B11 |
|--------------------------------------|-------------------|------------|------------|------------|
| Snap action contacts                 | List price        | \$ 54      | \$ 52      | \$ 51      |
|                                      | Operation diagram |            |            |            |
| Non-overlapping Slow action contacts | List price        | 58         | 55         | 55         |
|                                      | Operation diagram |            |            |            |
| Overlapping Slow action contacts     | List price        | 60         | 57         | 57         |
|                                      | Operation diagram |            |            |            |
| Slow action contacts                 | List price        | 60         | 57         | 57         |
|                                      | Operation diagram |            |            |            |
| Slow action contacts                 | List price        | 60         | 57         | 57         |
|                                      | Operation diagram |            |            |            |
| Snap action contacts                 | List price        | 60         | 57         | 57         |
|                                      | Operation diagram |            |            |            |
| Weight (packing per unit)            | kg                | 0.335      | 0.320      | 0.325      |

**Dimensions (mm)**

