

# Components

## IP66, UL Type 4X

### 60mm

⊕ "N.C." contact with positive opening operation or element (subassembly, head, lever) suitable for positive opening operation.

**Warning! The positive opening operation of limit switch is only guaranteed if the elements noted with ⊕ are fitted.**



LSTE61



LSTE71



LSTE93



LSTE40



LSA40X42



LSTE50




LSA40X53



LSA40X62

#### Contact blocks



B11 D11 C11 L02 L20 B02

Positive opening operation

Actuation speed max. m/s

Unit weight kg (1 pc)

Catalog number

List price

#### To be actuated by fully directional translation movement

Stainless steel flexible lever with insulated end ①	⊕	1	0.145	LSTE61	\$ 29
Stainless steel coil spring lever ①	⊕	1	0.152	LSTE62	29
∅ 3mm adjustable stainless steel rod lever, 195mm ①	⊕	1	0.150	LSTE71	26
∅ 3mm adjustable polyamide rod lever, 195mm ①	⊕	1	0.145	LSTE72	26
∅ 6mm adjustable fiberglass rod lever, 195mm ①	⊕	1	0.149	LSTE73	27

#### Multidirectional angular motion head (to be actuated by fully directional translation movement)

Stainless steel spring rod	⊗	1	0.066	LSTE91	17
Stainless steel flexible rod with insulated end	⊗	1	0.068	LSTE92	19
Stainless steel coil spring rod	⊗	1	0.075	LSTE93	18

#### Angular motion head without actuator, for non-adjustable roller levers (delivered with M5 nylon stop nut)

	⊕	1.5	0.102	LSTE40	20
--	---	-----	-------	--------	----

#### Actuator for angular motion head LSTE40

∅ 22mm polyamide roller lever ①	⊕	—	0.032	LSA40X41	6
∅ 22mm stainless steel roller lever ①	⊕	—	0.042	LSA40X42	14
∅ 22mm steel ball-bearing roller lever ①	⊕	—	0.044	LSA40X43	9
∅ 45mm rubber roller lever ①	⊗	—	0.050	LSA40X44	8

#### Angular motion head without actuator for flexible or adjustable levers (delivered with M5 nylon stop nut & adaptation parts)

	⊗	1 - 1.5 ②	0.121	LSTE50	22
--	---	-----------	-------	--------	----

#### Actuators for angular motion head LSTE50

∅ 22mm adjustable polyamide roller lever ①	⊗	—	0.023	LSA40X51	5
∅ 22mm adjustable stainless steel roller lever ①	⊗	—	0.032	LSA40X52	13
∅ 45mm adjustable steel ball-bearing roller lever ①	⊗	—	0.034	LSA40X53	9
∅ 45mm adjustable rubber roller lever ①	⊗	—	0.039	LSA40X54	7
Stainless steel flexible lever with insulated end ①	⊗	—	0.017	LSA40X61	7
Stainless steel coil spring lever ①	⊗	—	0.023	LSA40X62	7
∅ 3mm adjustable stainless steel rod lever, 195mm ①	⊗	—	0.014	LSA40X71	4
∅ 6mm adjustable polyamide rod lever, 195mm ①	⊗	—	0.010	LSA40X72	4
∅ 6mm adjustable fiberglass rod lever, 195mm ①	⊗	—	0.014	LSA40X73	5

① Free position adjustment of lever 9° by 9° over 360°.

② According to lever.