

Assembled 30mm, IP 65, UL Type 4

Movement to be detected

Key translation, on end or lateral

On end



Operating head type

	Right angle key	Straight key	Plain thermoplastic plunger	Plain steel plunger
Conformity / (N.C. contact with positive opening operation)			EN 50 047	EN 50 047
Maximum actuation speed m/s	0.5	0.5	0.5	0.5
Min. force: - actuation N	18	18	9	9
- positive opening operation N	60	60	44	44

9

Operating head type	Catalog number List price	LS35P15B11 \$ 31	LS35P16B11 \$ 33	LS35P10B11 \$ 22	LS35P11B11 \$ 22
Snap action contacts 	Catalog number List price	LS35P15D11 33	LS35P16D11 35	LS35P10D11 23	LS35P11D11 23
Non-overlapping Slow action contacts 	Catalog number List price	LS35P15C11 34	LS35P16C11 36	LS35P10C11 24	LS35P11C11 24
Overlapping Slow action contacts 	Catalog number List price	LS35P15L02 34	LS35P16L02 36	LS35P10L02 24	LS35P11L02 24
Slow action contacts 	Catalog number List price	LS35P15L20 34	LS35P16L20 36	LS35P10L20 24	LS35P11L20 24
Slow action contacts 	Catalog number List price	LS35P15B02 34	LS35P16B02 36	LS35P10B02 24	LS35P11B02 24
Snap action contacts 	Weight (packing per unit) kg	0.085	0.085	0.065	0.070

Approximate dimensions (mm)

