

Latch key safety limit switches 30mm

Movement to be detected

Small Latch (Key), Front or Vertical Translation

Casing

- Plastic
- 30 mm width
- Degree of protection IP65



Actuator

9

		Right angle key (22 mm mounting)	Straight key (22 mm mounting)
NC contact with positive opening operation		⊖	⊖
Actuation speed: maximal / minimal		0.5 / 0.01	0.5 / 0.01
Min. force: – for insertion of the key		15	15
– for extraction of the key		10	10
– positive opening operation		30	30
Non-overlapping slow action contacts	Catalog number List price	LS35P80D11-S \$ 43	LS35P80D11-S \$ 43
	Operation diagram		
Overlapping slow action contacts	Catalog number List price	LS35P80C11-S 43	LS35P80C11-S 43
	Operation diagram		
Simultaneous slow action contacts	Catalog number List price	LS35P80L02-S 43	LS35P80L02-S 43
	Operation diagram		
Weight with 1/2" NPT adaptor (packing per unit)	kg	0.087	0.087
Small Latch (Key)			
To order separately	Catalog number List price	LSA30P03 5	LSA30P04 5
Weight (packing per unit)	kg	0.009	0.009

Accessories, special contact arrangement or particular function: please consult us.

Dimensions (in mm)

