

Rotative axis safety limit switches 30mm

Movement to be detected

Angular Around Rotative Axis


Casing












- Plastic
- 30 mm width
- Degree of protection IP65



9

Actuator

"N.C." contact with positive opening operation 
 Actuation speed: maximal / minimal m/s
 Min. torque: – actuation N.m
 – positive opening operation N.m

| | | Galvanized steel rotative axis | Stainless steel rotative axis |
|-------------------------------------------------------------------------------------|------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| | |  |  |
| | | 0.5 / 0.01 | 0.5 / 0.01 |
| | | 0.12 | 0.12 |
| | | 0.60 | 0.60 |
| Non-overlapping slow action contacts | Catalog number List price | LS35P75D11-S \$ 51 | LS35P76D11-S \$ 57 |
|  | Operation diagram |  |  |
| Overlapping slow action contacts | Catalog number List price | LS35P75C11-S 51 | LS35P76C11-S \$ 57 |
|  | Operation diagram |  |  |
| Simultaneous slow action contacts | Catalog number List price | LS35P75L02-S 51 | LS35P76L02-S \$ 57 |
|  | Operation diagram |  |  |
| Weight with 1/2" NPT adaptor (packing per unit) kg | | 0.097 | 0.097 |

Accessories, special contact arrangement or particular function: please consult us.

Dimensions (in mm)

