


Disconnect switches
Non-fusible

16A – 100A, Base & DIN rail mounted 3 Pole transfer switches

For a complete assembly,
please select one of each:

- 1 switch
- 1 handle
- 1 shaft




OT45E3C



OXP5X170



OHB_J5



OT45E3C



OHB2AJE011



OHB_J5



OHY_J5



OXS5X_

16 – 100 Amp – 600V, 3 Pole transfer switches ①

UL general purpose amp rating	IEC AC21 amp rating	Maximum horsepower ratings						Terminal lugs		Shaft size (mm)	Catalog number	List price
		Single phase		Three phase			Wire size	Wire type				
		120V	240V	200V	240V	480V	600V					
UL 508	16	1	2	3	5	10	10	#18 – 8	Cu	5	OT16E3C	\$ 258
	25	1.5	3	7.5	7.5	15	20				OT25E3C	270
	40	2	5	10	10	20	25				OT32E3C	288
UL 98	60	2	5	15	15	30	30	#14 – 1	Cu	5	OT45E3C	328
	80	2	5	20	20	40	40				OT63E3C	368
	30	2	5	10	10	20	30				OT30E3C	428
	60	3	7.5	20	20	40	40	#14 – 4	Cu	5	OT60E3C	478
	100	5	15	25	30	50	50				OT100E3C	514

Selector handles — 5mm, for use with transfer switches; marked I/ON - O/OFF - II/ON

UL/NEMA type	IEC type	Color	Defeatable	Padlockable	Weight (lbs.)	Catalog number	List price
1, 3R, 12	IP65	Black Red/Yel	Yes	Yes	0.16	OHB2AJE011② OHY2AJE011②	\$ 40

Shafts for selector handles — 5mm, for use with transfer switches

Shaft length (inches/mm)	Mounting depth② (inches)			Weight (lbs)	Shaft size (mm)	Catalog number	List price
	OT16E3C OT25E3C OT32E3C	OT45E3C OT63E3C	OT30E3C OT60E3C OT100E3C				
3.3/85	3.6 - 4.3	4.4 - 5.0	3.9 - 4.9	0.04	5	OXS5X85	\$ 4
4.1/105	4.4 - 5.1	5.1 - 5.8	4.7 - 5.7	0.04		OXS5X105	4
4.7/120	5.0 - 5.8	5.7 - 6.4	5.3 - 6.3	0.05		OXS5X120	4
5.1/150	5.4 - 6.1	6.1 - 6.8	5.6 - 6.7	0.05		OXS5X150	6
7.1/180	7.4 - 8.1	8.1 - 8.7	7.6 - 8.6	0.08		OXS5X180	6
9.8/250	10.1 - 10.8	10.9 - 11.5	10.4 - 11.4	0.1		OXS5X250	12
13/330	13.3 - 14.0	14.0 - 14.7	13.5 - 14.5	0.14		OXS5X330	20

Pistol handles — 5mm, for use with transfer switches; marked I/ON - O/OFF - II/ON

UL/NEMA type	IEC type	Color	Length in/mm	Defeat-able	Padlock-able	Weight (lbs)	Shaft size (mm)	Catalog number	List price
1, 3R, 12	IP65	Black Red/Yel	2.6/65	Yes	Yes	0.29	5	OHB65J5E011 OHY65J5E011	\$ 90
1, 3R, 4, 4X, 12	IP66	Black Red/Yel	2.6/65	Yes	Yes	0.29	5	OHB65L5E011 OHY65L5E011	130

Shafts for pistol handles — 5mm, for use with transfer switches

Shaft length (inches/mm)	Mounting depth② (inches)			Weight (lbs)	Shaft size (mm)	Catalog number	List price
	OT16E3 OT25E3 OT32E3	OT45E3 OT63E3	OT30E3 OT60E3 OT100E3				
5.9/160	7.2	7.4	7.5	0.07	5	OXPS5X150	\$ 14
6.7/170	8.0	8.2	8.3	0.08		OXPS5X170	16
10.4/265	11.7	11.9	12.0	0.12		OXPS5X265	18
15.8/400	17.0	17.2	17.3	0.18		OXPS5X400	30
19.7/500	21.0	21.2	21.3	0.23		OXPS5X500	42

① A snap on power pole may be added to build a 4 pole transfer switch; please reference accessories and auxiliary contact information on page 18.12.

② Not suitable for use with OT30E3C, OT60E3C, OT100E3C.

③ Mounting depth is the distance from the outside of door to the disconnect switch mounting plate. Shaft can be cut to desired length.