



Technical data

PST30 – 300

PSTB370 – 1050

Softstarters
Type PST

Cross section of connectable cables

		Type of softstarter				
		PST30 ... 72	PST85 ... 142	PST175 ... 300	PSTB370 ... 470	PSTB570 ... 1050
Main circuit						
Available terminals:	L1, L2, L3 T1, T2, T3	Yes Yes	Yes Yes	Yes Yes	Yes Yes	Yes Yes
(For external by-pass):	B1, B2, B3	Yes	Yes	Yes	No	No
Connection clamp						
Solid/Stranded	1 x mm ²	10 ... 95	See page 6.31	See page 6.31	See page 6.31	See page 6.31
Solid/Stranded	1 x mm ²	6 ... 35	See page 6.31	See page 6.31	See page 6.31	See page 6.31
Tightening torque (recommended), Nm		6.0	See page 6.31	See page 6.31	See page 6.31	See page 6.31
Connection bar		No				
Width and thickness	mm	–				
Hole diameter	mm	–				
Tightening torque (recommended), Nm		–	9	18	40	49
Supply and control circuit						
Connection clamp		Yes	Yes	Yes	Yes	Yes
Solid/Stranded	1 x mm ²	2.5	2.5	2.5	2.5	2.5
Solid/Stranded	1 x mm ²	1.5	1.5	1.5	1.5	1.5
Tightening torque (recommended), Nm		0.5	0.5	0.5	0.5	0.5

6

Fuse ratings and power losses

For softstarter	Recommended ABB Overload protection		Max power loss at rated I _e W	Maximum fuse ratings - main circuit			Ferraz fuses		Power requirements supply circuit VA/VA pull in
	Type	Current range A		A	Type	Holder	A	Type	
PST									
PST30	Integrated	9... 35	100	80	170M1366	170H1007	100	6.6 URB 000 D08V 0100	5
PST37	Integrated	12...46	120	125	170M1368	170H1007	160	6.6 URB 000 D08V 0160	5
PST44	Integrated	15...58	140	160	170M1369	170H1007	200	6.6 URD 30 D08A 0200	5
PST50	Integrated	15...58	160	160	170M1369	170H1007	200	6.6 URD 30 D08A 0200	5
PST72	Integrated	23...86	230	250	170M1371	170H1007	315	6.6 URD 30 D08A 0315	5
PST85	Integrated	30...115	270	315	170M1372	170H1007	400	6.6 URD 30 D08A 0400	10
PST105	Integrated	38...144	325	400	170M3019	170H3004	400	6.6 URD 30 D08A 0400	10
PST142	Integrated	45...173	435	450	170M3020	170H3004	500	6.6 URD 30 D08A 0500	10
PST175	Integrated	60...230	540	500	170M3021	170H3004	550	6.6 URD 30 D08A 0550	15
PST210	Integrated	75...288	645	630	170M5012	170H3004	630	6.6 URD 31 D08A 0630	15
PST250	Integrated	75...288	765	700	170M5013	170H3004	630	6.6 URD 31 D08A 0630	15
PST300	Integrated	90...345	920	900	170M5015	170H3004	900	6.6 URD 31 D11A 0900	15
PSTB – 600V									
PSTB370	Integrated	120...460	90	700	170M5013	170H3004	630	6.6 URD 31 D08A 0630	20/480
PSTB470	Integrated	150...575	110	900	170M5015	170H3004	900	6.6 URD 31 D11A 0900	20/480
PSTB570	Integrated	180...690	105	900	170M5015	170H3004	900	6.6 URD 31 D11A 0900	25/900
PSTB720	Integrated	225...863	110	1250	170M5018	170H3004	1250	6.6 URD 33 D11A 1250	25/860
PSTB840	Integrated	300...1160	170	1500	170M5018	170H3004	1600	6.6 URD 33 D11A 1250	25/860
PSTB1050	Integrated	360...1380	170	1800	170M6020	170H3004	2000	6.6 URD 233 PLAF 2000	25/860
PSTB – 690V									
PSTB370	Integrated	120...460	90	700	170M5013	170H3004	630	6.6 URD 31 D08A 0630	20/480
PSTB470	Integrated	150...575	110	900	170M5015	170H3004	900	6.6 URD 31 D11A 0900	20/480
PSTB570	Integrated	180...690	105	900	170M5015	170H3004	900	6.6 URD 31 D11A 0900	25/900
PSTB720	Integrated	225...863	110	1250	170M6018	170H3004	1250	6.6 URD 33 D11A 1250	25/860
PSTB840	Integrated	300...1150	170	1500	170M6018	170H3004	1600	6.6 URD 33 TTFA 1600	25/860
PSTB1050	Integrated	360...1380	170	1600	170M6019	170H3004	1600	6.6 URD 33 TTFA 1600	25/860