

Components

40mm, IP 65, UL Type 4



LS45P00B11

Bodies with contact block for rectilinear or angular motion heads

	LS	45	P	00	B	11
Limit Switch.....	LS					
Casing width 40 mm		3				
Cable inlet						
1 cable inlet for Pg 13.5 cable gland				0		
1 cable inlet M20 x 1.5 for ISO 20 cable gland				3		
1 cable inlet for 1/2" NPT				5		
Plastic casing.....			P			
Without operating head						00
						Contacts
						11 1 N.O. + 1 N.C. contacts
						02 2 N.C. contacts
						20 2 N.O. contacts
						Snap action
						B Zb Snap
						Dependent (slow) action
						L Zb Slow / Simultaneous
						D Zb Non-overlapping late make
						C Zb Overlapping early make



LSTH41

Operating heads

	LS	T	H	41
Limit Switch.....	LS			
Operating head		T		
For plastic casing 40 mm width				40
				References of heads
				11 ... 14, 19 with rectilinear movement (plain plunger, steel ball plunger or roller plunger)
				31 ... 37 with rectilinear movement (roller lever on steel plunger)
				40 with angular movement (without actuator) actuator to be ordered separately
				41 ... 44 with angular movement (roller lever)
				50 with angular movement (without actuator) actuator to be ordered separately
				51 ... 54 with angular movement (adjustable roller lever)
				61, 62 flexible lever (spring)
				71, 72, 73 adjustable lever (rod)
				91 ... 93 multidirectional angular movement (spring rod)



LSA40X51

Separate actuators (roller lever, adjustable roller or rod levers, etc.)

	LS	A	40	X	51
Limit Switch.....	LS				
Actuator (roller)		A			
Casing width: 40 mm			40		
					Reference of actuators
					41 ... 44 non-adjustable roller lever
					51 ... 54 adjustable roller lever
					61, 62 flexible lever (spring)
					71, 72, 73 adjustable lever (rod)
					For casing
					M Metal
					P Plastic
					X Plastic or metal

Separate contact blocks

	LS	C	40	X	C	11
Limit Switch.....	LS					
Contact blocks		C				
Casing width: 40 mm			40			
For casing						
Metal.....					M	
Plastic.....					P	
Plastic or metal.....					X	
						Contacts
						11 1 N.O. + 1 N.C. contacts
						02 2 N.C. contacts
						20 2 N.O. contacts
						Snap action:
						B Zb Snap
						Dependent (slow) action:
						L Zb Slow / Simultaneous
						D Zb Non-overlapping late make
						C Zb Overlapping early make



LSC40XC11