

Components

IP66, UL Type 4X

60mm


Metal
Limit switches

⊖ "N.C." contact with positive opening operation or element (subassembly, head, lever) suitable for positive opening operation.

Warning! The positive opening operation of limit switch is only guaranteed if the elements noted with ⊖ are fitted.



LSTE61



LSTE71

LSTE93



LSTE40

LSA40X42




LSTE50



LSA40X53

LSA40X62

Contact blocks



Positive opening operation

Actuation speed max. m/s

Unit weight kg (1 pc)

Catalog number

List price

To be actuated by fully directional translation movement

Stainless steel flexible lever with insulated end ①	⊖	1	0.145	LSTE61	\$ 29
Stainless steel coil spring lever ①	⊖	1	0.152	LSTE62	29
∅ 3mm adjustable stainless steel rod lever, 195mm ①	⊖	1	0.150	LSTE71	26
∅ 3mm adjustable polyamide rod lever, 195mm ①	⊖	1	0.145	LSTE72	26
∅ 6mm adjustable fiberglass rod lever, 195mm ①	⊖	1	0.149	LSTE73	27

Multidirectional angular motion head (to be actuated by fully directional translation movement)

Stainless steel spring rod	⊗	1	0.066	LSTE91	17
Stainless steel flexible rod with insulated end	⊗	1	0.068	LSTE92	19
Stainless steel coil spring rod	⊗	1	0.075	LSTE93	18

Angular motion head without actuator, for non-adjustable roller levers (delivered with M5 nylostop nut)

	⊖	1.5	0.102	LSTE40	20
--	---	-----	-------	--------	----

Actuator for angular motion head LSTE40

∅ 22mm polyamide roller lever ①	⊖	—	0.032	LSA40X41	6
∅ 22mm stainless steel roller lever ①	⊖	—	0.042	LSA40X42	14
∅ 22mm steel ball-bearing roller lever ①	⊖	—	0.044	LSA40X43	9
∅ 45mm rubber roller lever ①	⊗	—	0.050	LSA40X44	8

Angular motion head without actuator for flexible or adjustable levers (delivered with M5 nylostop nut & adaptation parts)

	⊗	1 - 1.5 ②	0.121	LSTE50	22
--	---	-----------	-------	--------	----

Actuators for angular motion head LSTE50

∅ 22mm adjustable polyamide roller lever ①	⊗	—	0.023	LSA40X51	5
∅ 22mm adjustable stainless steel roller lever ①	⊗	—	0.032	LSA40X52	13
∅ 45mm adjustable steel ball-bearing roller lever ①	⊗	—	0.034	LSA40X53	9
∅ 45mm adjustable rubber roller lever ①	⊗	—	0.039	LSA40X54	7
Stainless steel flexible lever with insulated end ①	⊗	—	0.017	LSA40X61	7
Stainless steel coil spring lever ①	⊗	—	0.023	LSA40X62	7
∅ 3mm adjustable stainless steel rod lever, 195mm ①	⊗	—	0.014	LSA40X71	4
∅ 6mm adjustable polyamide rod lever, 195mm ①	⊗	—	0.010	LSA40X72	4
∅ 6mm adjustable fiberglass rod lever, 195mm ①	⊗	—	0.014	LSA40X73	5

① Free position adjustment of lever 9° by 9° over 360°.

② According to lever.