


# Assembled 30mm, IP 65, UL Type 4

Plastic  
Limit switches

## Movement to be detected



## Operating head type

	Adjustable $\varnothing$ 3 stainless steel rod lever	Adjustable $\varnothing$ 3 fiber-glass rod lever	Spring rod	Flexible rod with insulated end
Conformity / $\text{N.C.}$ (N.C. contact with positive opening operation)				
Maximum actuation speed	m/s 1.5	1.5	1	1
Min. torque: - actuation	N.m 0.10	0.10	0.12	0.12
- positive opening operation	N.m —	—	—	—

9

	Catalog number	LS35P71B11	LS35P72B11	LS35P91B11	LS35P92B11
Snap action contacts	List price	\$ 27	\$ 27	\$ 25	\$ 25
	Operation diagram				
Non-overlapping Slow action contacts	Catalog number	LS35P71D11	LS35P72D11	LS35P91D11	LS35P92D11
List price	28	28	27	27	
	Operation diagram				
Overlapping Slow action contacts	Catalog number	LS35P71C11	LS35P72C11	LS35P91C11	LS35P92C11
List price	29	29	27	27	
	Operation diagram				
Slow action contacts	Catalog number	LS35P71L02	LS35P72L02	LS35P91L02	LS35P92L02
List price	29	29	27	27	
	Operation diagram				
Slow action contacts	Catalog number	LS35P71L20	LS35P72L20	LS35P91L20	LS35P92L20
List price	29	29	27	27	
	Operation diagram				
Snap action contacts	Catalog number	LS35P71B02	LS35P72B02	LS35P91B02	LS35P92B02
List price	29	29	27	27	
	Operation diagram				
Weight (packing per unit)	kg	0.100	0.100	0.080	0.080

## Dimensions (mm)

